

Oase

AquaMax Eco Premium 12 V



- The safe 12 V technology is perfect for implementation in swim ponds and bathing ponds
- Outstanding energy balance: reliable displacement using even less energy
- Supplemental, patented connection of filter accessories for debris supply from more distant pond zones
- Elegant design with clever operating elements
- Maximum convenience thanks to ergonomic and easily accessible handles
- »Environmental Function Control« (EFC by OASE) protects against dry run and blocking
- MADE IN GERMANY: precise and reliable German engineering at a high level of quality



		AquaMax Eco Premium 6000 / 12 V	AquaMax Eco Premium 12000 / 12 V
Dimensions (L x W x H)	mm	340 x 280 x 165	
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / DC	
Power consumption	W	55	100
Cable length 12 V-device	m	2.50 (Power unit) + 8.00	
Net weight	kg	8.7	10.6
Guarantee (+ extended guarantee on request)	Years	3 + 2	
Max. flow rate	l/min	100	190
Max. flow rate	l/h	6000	11400
Max. head height	m	3.2	
Connection pressure-side	mm	50	
Connection pressure-side		2"	
Connection suctions-side	mm	50	
Connection suctions-side		2"	
Connection for hoses	mm	25 / 32 / 38	25 / 32 / 38 / 50
Connection for hoses		1", 1 ¼", 1 ½"	1", 1 ¼", 1 ½", 2"
Filter intake surface	cm²	1000	
Coarse debris displacement max.	mm	10	11
Electronically adjustable		No	
Setup type		Can be setup underwater & dry	