

Oase

MudDrain



- Adjustable handle: Easy and reliable positioning of the float in different positions.
- Convenient mounting on the connection of the pressure port positioned on top, through flipping it up
- Can be unscrewed for permanent installation
- Groove for rope fixation
- For coarse debris: All models pump water with debris up to 30 mm in diameter
- "A cool head": Optimal heat dissipation of the motor thanks to water cooling, in conjunction with the stainless steel housing

		ProMax MudDrain 7000	ProMax MudDrain 11000	ProMax MudDrain 14000	ProMax MudDrain 20000	ProMax MudDrain 25000	ProMax MudDrain 30000
Flow rate Q max.	l/h	7500	11500	14500	20000	25000	30000
Delivery head – H max.	m	5	7	11	10		12
Pressure – max.	bar	0.5	0.7	1.1	1		12
Power consumption	W	325 W	625 W	950 W		1200 W	1500 W
Rated voltage		230 V / 50 Hz					
Guarantee (+ request guarantee)	Years	2 + 1 Years					
Immersion depth max.	m	7					
Grain size – max.	mm	30		35		40	
Automatic function		Float Switch					
Pressure-side connection		1½"				2"	
Power cable length	m	10					
Protection class		IP68					
Net weight	kg	5.6 kg	6.8 kg	8.2 kg	8.1 kg	13.4 kg	14.1 kg
Dimensions (L x W x H)	mm	193 x 247 x 395	193 x 247 x 422		200 x 254 x 440	178 x 246 x 453	