

# Oase

## Oase ProfiSkim wall 100 (PNF6598)



ProfiSkim Wall 100

Dimensions (L x W x H)	mm	273 x 267 x 408
Net weight	kg	2.80
Guarantee	Years	3 + 2
Possible Water level difference		120mm
Skimmer opening width	mm	210
Pond surface, max.	m <sup>2</sup>	30
Pump capacity, min.	l/h	6000
Pump capacity, max.	l/h	16000
Rec. flow rate (gravitation)	l/h	12000
Connections, outlet		DN110

- Powerful debris removal from pond surfaces
- Optimal flow-through thanks to DN 110 connection
- The technology is protected through an integrated debris basket with wildlife evacuation system
- Skims off debris from a pond surfaces of up to 30 m<sup>2</sup>
- For permanent installation in a wall
- The debris basket is easy to take out for effortless cleaning from the front and from the top
- With useful accessories (optional): Wall extension, wide-mouth extension, height extension and high-quality stainless steel covers.



### Wide-mouth extension

More efficient debris removal thanks to the helpful wide-mouth extension.



### Skimmer extension

Practical skimmer extension for installations.



### Height extension

Versatile installation under a terrace or a wooden walkway – the height extension compensates for height differences.



### Stainless steel cover, standard

The high-quality stainless steel cover ensures a sophisticated look.



### Stainless steel cover, wide

The high-quality stainless steel cover ensures a sophisticated look.