HUNZA

Hunza eyelid step light (seamless) - black



COLOURPRODUCT CODEBEAM ANGLEWATTAGELIFE OF LAMPN/ALGH321038°20W5000h

| CEN | IED | ΛΙ |
|-----|-----|----|

| Construction Material | Powder coated alumin | nium | | |
|------------------------------|--|--|---------------------------------------|--|
| Cut-out (mm) | 64 | | | |
| IP rating | 66 | | | |
| Rotation angle (°) | N/A | | | |
| Tilt angle (°) | N/A | | | |
| Weight (g) | 465 | | | |
| Wiring | | | | |
| Cable\flying lead | 1m - H07 Rubberised | | | |
| Type of wiring required | Parallel | | | |
| Transformers | | | | |
| Product code | Description | Product code | Description | |
| LGT1101 | Single light fused outdoor transformer | LGT1103 | Three light fused outdoor transformer | |
| LGT1102 | Two light fused outdoor transformer | LGT1104 | Four light fused outdoor transformer | |
| Accessories | | | | |
| Product code | Description | | | |
| ELA7924 | Flexible conduit 20mr | Flexible conduit 20mm (16mm ID) black - 50mm | | |
| ELC1022 | Black rubber cable 2-core - 1mm - 50m | | | |
| Warranty | | | | |
| Body | Internal | Internal | | |
| 5 year | 5 year | | | |