






OBLIX S 15 930 N

15112 9300 N

AVAILABLE IN
DARK GREY 15112 9300 N



[View on website](#)



General info

LOCATION	exterior
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	812lm // 7,1W // 115lm/W
LED Technics (luminaire)	575lm // 8W // 70lm/W


Options

PIN 17
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [15112_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Waterproof connection parts

☐☐☐

Pins and plates for bollards

☐

Notes: