





OBLIX 70 930 N

220 77 811 930 N

AVAILABLE IN

ALU GREY 220 77 811 930 A

DARK GREY 220 77 811 930 N



[View on website](#)

General info

LOCATION	exterior
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	3,5
ADJUSTABILITY	non adjustable
INFORMATION	INCL LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	812lm // 7,1W // 115lm/W
LED Technics (luminaire)	591lm // 8W // 72lm/W


Options

PLATE 7
PIN 12
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P


For detailed installation instructions, please consult the manual: [220_77_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

☐


216 12 01 IP68 CONNECTION KIT

☐


216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 01 12 PIN 12

☐

229 02 07 PLATE 7

☐

Notes: