

HUB-50 & HUB-100

SYSTEM

The HUB-50 has a maximum installation value of 50VA. The HUB-100 has a maximum installation value of 100VA.

High-impact plastic casing

Equipped with light signal that blinks when, for example, an overload or improper installation is detected, so that this can be avoided

Motion Detection
- Light switches on for 1, 3 or 9 minutes
Operated with the "Motion Detection" button

Touch screen with following functions:

- Permanent on
- Dusk till dawn
- 1 to 12 hours on
- Motion Detection
- Permanent off

Operated with the "On" button

Two cable entries for the in-lite ground cables with Easy-Connect click closure. Cover cap with magnetic closure

Connection for light sensor

Connection for Motion Detector MOVE

100-230V power cable

MOVE & LIGHT SENSOR

SYSTEM & ACCESSORY



Motion Detector MOVE

Accessory suitable for use with the HUB-50 and HUB-100. MOVE detects movement up to 12 meters at a vertical angle of 40 degrees and horizontal angle of 105 degrees. MOVE comes with a two-meter cable that can be extended to up to 20 meters using the MOVE-EXT CORD.



Light sensor

Standard feature of the HUB-50 and HUB-100. Detects light and dark for the following functions:
Day/night switch and timer. Install the light sensor where it cannot be influenced by artificial light.