

Oase

AquaMax Eco Expert



- New, energy-efficient pump generation for extremely powerful and economic delivery capacity
- Perfect for use in demanding filter systems or for large watercourses and waterfalls
- Excellent efficiency and at the same time outstanding displacement of coarse debris down to 11 mm in size
- Robust and durable stainless steel housing for stability
- Unique, patented frost protection: Consequently, the pump will not be damaged at temperatures as low as -20°C
- Protection against dry run and blocking through Environmental Function Control (EFC by OASE)
- Can be setup underwater & dry
- The pump is unusually quiet in operation; ideal for use in a pump chamber
- Patented »Seasonal Flow Control« for intelligent and environmentally-conscious regulation of flow rate and delivery head
- An additional 30% energy savings is possible with SFC switched on



		AquaMax Eco Expert 21000	AquaMax Eco Expert 26000	AquaMax Eco Expert 36000	AquaMax Eco Expert 44000
Dimensions (Ø x H)	mm	490 x 215 x 210			540 x 250 x 220
Rated voltage		220 - 240 V / 50/60 Hz			
Power consumption	W	40 - 350	60 - 440	90 - 540	140 - 700
Power cable length	m	10.00			
Net weight	kg	12.00			14.90
Guarantee	Years	3 + 2			
Max. flow rate	l/min	350	433	600	733
Max. flow rate	l/h	21000	26000	36000	44000
Max. head height	m	8.00	8.50	9.00	9.50
Connection pressure-side	mm	50			
Connection pressure-side		2"			
Connection sunctions-side	mm	50		63	
Connection sunctions-side		2"		2 ½"	
Connection for hoses	mm	38 / 50			
Connection for hoses		1 ½", 2"			
Filter intake surface	cm²	1060		1120	
Coarse debris displacement max.	mm	11			
Connection EGC		Yes			
Electronically adjustable		Yes			
Setup type		Can be setup underwater & dry			