
Oase

LunAqua 3 LED (LGF9140)





- Bright illumination, thanks to a powerful 110 lumen rating
- High energy efficiency at power consumption of 3 watt
- Half peak angle of 30° for broad illumination of plants and other highlights
- Adjustable head for flexible alignment of the beam angle
- Suitable for permanent underwater use, thanks to protection class IP68 (connection IP 44)
- Suitable for use underwater and above the water
- Fast and easy installation thanks to Plug'n Play
- Included in the scope of delivery: 1 or 3 spotlights, 12 V transformer, rubber hose line, 1 or 3 ground stakes



		LunAqua 3 LED Set 1	LunAqua 3 LED Set 3
Dimensions (L x W x H)	mm	75 x 140	
Rated voltage (primary, secondary)		230 V / 50 Hz, 12 V / AC	
Power consumption light fixture	W	3	
Energy efficiency category light fixture		А	
Power consumption set	W	4	10
Protection class		IP 68, IP 44 (power unit)	
cable length 12 V device	m	2.00 (power unit) + 5.00	
Net weight	kg	1.42	3.32
Gaurantee	Years	2	
Illumination type		LED	
Number of indvidual LEDs	EA	3	
Light flux	lm	110	
Light colour		Warm-white	
Colour temperature	k	3000	
Half peak angle		30 degrees	