

Oase

AquaOxy Pond Aerators



- Suitable for ponds up to 50 m³ or with high fish stock
- Special safe 12 volt technology for AquaOxy 1000 – 2000
- Optimal oxygen supply for pond flora and fauna
- Robust motor and high quality UV stabilised housing
- Reduced noise, energy efficient operation
- Flexible location thanks to long hose length
- Easy handling
- Included in the scope of delivery: Air stones and replacement membrane set



		AquaOxy 500	AquaOxy 1000	AquaOxy 2000
Dimensions (L x W x H)	mm	185 x 140 x 110	220 x 225 x 135	
Rated voltage (primary, secondary)		-	230 V / 50 Hz, 12 V / AC	
Rated voltage	W	230 V / 50 Hz	-	
Power consumption	m	8	15	25
Cable length 12 V device	kg	-		
Power cable length	Years	3.00		
Net weight	W	1.80	3.78	4.16
Guarantee		2		
Max. flow rate		500	1000	2000
Pressure	EA	0.2 / 2.00		0.25 / 2.50
Mechanical adjustment	EA	No	Yes	
Hose (quantity / length / diameter)	mm	2 pc / 5 m / 4.5 mm		
Number of outlets		2		
Suitable for ponds up to max.	EA	5.0	10.0	20.0
Outdoor suitability	mm	Unlimited		
Number of air stones		2		