

Oase

PondoVac 5 (PNF5064)



- Vacuum without interruption thanks to integrated emptying pump
- Flexible use – waste water can be diverted in any direction.
- Pumps the waste water even over height differentials
- Maximum suction depth of 2.5 m thanks to high performance 1700 W motor with optimised blade geometry
- Can be used for cleaning garden ponds, pools and swim ponds as well as a wet vacuum in the household
- Transparent suction tube for flow through control
- Easy to move with transport rollers and adjustable handle
- More ground clearance and silent tyres in Big Wheel design
- Hand regulator for adjusting the suction power
- Suction capacity up to 8000 l/h, depending on the implemen-tation conditions
- Discharge hose with C-connection on both sides
- Included in the scope of delivery: 4 robust aluminium tubes, special string algae nozzle, broadened universal nozzle, wet suction brush, brush nozzle, debris collection bag, 5 m long suction hose and 10 long discharge hose

		PondoVac 5
Dimensions (L x W x H)	mm	435 x 395 x 670
Rated voltage		230 V / 50 Hz
Power consumption	W	1700
Power consumption pump	W	900
Power cable length	m	7.50
Net weight	kg	27.00
Guarantee (+ request gaurantee) ^{*P293}	Years	2 + 1
Suction depth max.	m	2.50
Max. flow rate	l/h	8000
Length, suction hose	m	5
Length, discharge hose	m	10
Floating hose application	mm	38