

Oase

Vitronic Universal UVC clarifiers



- Suitable for ponds up to 60m²
- Elimination of suspended algae (green water)
- Reduction of harmful bacteria and pathogen level
- New: Direct installation on the BioSmart (only Vitronic 18 - 36W)
- Visual function check of the UVC bulb
- Quick release for easy bulb change and cleaning of the quartz glass
- High quality workmanship with impact resistant plastic housing
- Easy installation thanks to an extensive range of connection accessories
- Incl. high quality UVC bulb
- 100%, VDE-certified safety; does not cause eye injuries

		Vitronic 11 W	Vitronic 18 W	Vitronic 24 W	Vitronic 36 W	Vitronic 55 W
Dimensions (L x W x H)	mm	330 x 120 x 100		529 x 186 x 130		660 x 155 x 130
Rated voltage		230 V / 50 Hz		220 - 240 V / 50 / 60 Hz		
Power consumption	W	14	18	24	36	55
Power cable length	m	3.00		5.00		
Net weight	kg	1.36	2.12	2.25	2.28	2.30
Guarantee (+ request guarantee)*P.293	Years			2		
UVC power	W	11	18	24	36	55
Temperature display				No		
UVC operating hours meter				No		
Number of inlets	EA			1		2
Connections, inlet	mm	19 / 25 / 32 / 38		25 / 32 / 38		
Connections, inlet		3/4", 1", 1 1/4", 1 1/2"		1", 1 1/4", 1 1/2"		
Number of outlets	EA	1		2		1
Connections, outlets	mm	19 / 25 / 32 / 38		25 / 32 / 38		
Connections, outlets		3/4", 1", 1 1/4", 1 1/2"		1", 1 1/4", 1 1/2"		
Max. flow rate	l/h	1700	3500	4500	6000	8500
Max. operating pressure	bar	0.50		0.60		
Suitable for ponds up to max.	m ³	10.0	20.0	25.0	40.0	60.0
Suitable for ponds with fish stock	m ³	5.0	10.0	12.5	20.0	30.0
Suitable for ponds with koi ¹	m ³	2.5	5.0	6.5	10.0	15.0
Connection to		-		BioSmart 18000 / 36000, BioTec ScreenMatic ² 40000 - 60000		
Other				Visual function check		