

AquaMax Eco Premium



- Outstanding energy balance: Reliable displacement using even less energy
- Supplemental, patented connection of optional filter accessories for debris supply from more distant pond zones
- Unique, patented frost protection: Consequently, the pump will not be damaged at temperatures as low as -20°C
- Flow rate can be mechanically and electronically adjusted with the optional accessories InScenio Dimmer of FM-Master Elegant design with clever operating elements
- Quiet for dry set up on swim ponds and bathing ponds
- Plant remains or fish waste to 11 mm in size are displaced
- Environmental Function Control (EFC by OASE) protects against dry run and blocking
- MADE IN GERMANY: Precise and reliable German engineering art at a high level of quality

		AquaMax Eco Premium 4000	AquaMax Eco Premium 6000	AquaMax Eco Premium 8000	AquaMax Eco Premium 10000	AquaMax Eco Premium 12000	AquaMax Eco Premium 16000	AquaMax Eco Premium 20000
Dimensions (L x W x H)	mm	340 x 280 x 165						
Rated voltage		220 - 240 V / 50 / 60 Hz						
Power consumption	W	10 - 35	12 - 45	15 - 60	19 - 88	10 - 110	11 - 145	15 - 180
Power cable length	m	10.00						
Net weight	kg	5.30				5.40		5.70
Guarantee (+ request guarantee)	Years	3 + 2						
Max. flow rate	l/min	66	100	133	166	200	260	325
Max flow rate	l/h	4000	6000	8000	1000	12000	15600	19500
Max head height	m	3.30	3.70	4.10	4.70	5.00	5.20	5.40
Connection pressure-side	mm	50						
Connection pressure-side		2"						
Connection suctions-side	mm	50						
Connection suctions-side		2"						
Connections for hoses	mm	25/32/38		25/32/38/50				
Connections for hoses		1 , 1 1/4 , 1 1/2		1 , 1 1/4 , 1 1/2 2				
Filter intake surface	cm²	1000						
Course debris displacement max.	mm	10				11		
Electronic adjustment		Yes						
Electronic adjustment		Can be set up underwater & dry						